

Background of the Invention

It is known that metal shields may be disposed on the exterior circumferential surface of box-shaped insulative housings of connectors for the purposes of preventing interference, such as electrical noise. One example of such a connector is disclosed in Japanese Utility Model Application Laid-Open No. Hei 5-34679, Japanese Patent Application Laid-Open No. Hei 10-83866, and others. The connector disclosed in these publications is one that is mounted to a substrate such as a printed circuit board and is formed so that a pair of substantially U-shaped shield members made of metal plates are overlapped on four or three surfaces of the exterior of a substantially box-shaped insulative connector housing.

FIGS. 15 and 16 of this application show such a conventional shielded connector. FIG. 15 illustrates a receptacle style connector **R**, while FIG. 16 illustrates a plug style connector **P**. The receptacle connector **R** is typically smaller in size than the plug connector **P**, so it should be understood that the drawings are not to scale and that the representative size of the receptacle connector **R** has been enlarged for clarity.

As for the receptacle connector **R** of FIG. 15, the shield of the connector is composed of a metal shell 320 that is disposed on the outer surface of the connector housing. It is shaped in a substantially U-shape as viewed from the top and the connector shield also includes a metal shield plate 330 that is U-shaped in cross-section that is disposed between the metal shell 320 and the connector insulative housing. The metal

shell 320 is formed so as to cover three surfaces, i.e., the front surface and both side surfaces of the insulative housing, while the shield metal plate 330 is disposed to cover three surfaces, i.e., the top surface and both side surfaces of the insulating housing. Thus four surfaces of the connector housing are actually covered with the shield, i.e., the front surface, the top surface and both side surfaces. An engagement piece 303 is provided on the metal shield plate 320 that is engaged with an engagement recess portion 311 of a terminal portion 310 that serves as a metal shield for opposing the plug connector **P**.

The metal shell 320 has a front surface shield portion 323 and side surface shield portions 324 on both sides of the connector. An engagement sleeve portion 307 has an opening 321 into which the terminal portion 310 of the plug connector **P** is inserted, and is provided in the front surface 323 of the shield portion. As illustrated, the engagement sleeve portion 307 is formed substantially into a rectangular sleeve shape so that it projects outwardly on the front surface of the connector. This metal shell 320 is typically formed by drawing that specific portion of the engagement sleeve portion 307, after the entire metal shield plate has been stamped out from a blank. A convex portion 308 may be formed as a polarizing portion that is engaged with a recess 312. Conductive terminals 313, having contact portions are arranged within the plug connector **P**.

Connectors such as those shown in FIGS. 15 & 16 tend to be small in size, as well as the circuit boards upon which they are mounted. However, it is desirable to reduce the manufacturing cost of such connectors without losing the dimensional stability of the connector. Thus, it is a goal of this invention to keep the connector small in size while maintaining the dimensional stability of the shield and retaining its electrical properties.

However, in the prior art connectors described above and shown in FIGS. 15 & 16, there is a problem. The manufacturing cost of these connectors is high because the engagement sleeve portion 307 is formed by drawing. The outer profile of these connectors is also increased because of this drawn structure, resulting in difficulty in achieving the goal of miniaturization. The engagement sleeve portion 307 is formed by

drawing so that there is a problem that the sleeve portion 307 does not have satisfactory dimensional stability. Furthermore, a large force, such as a twisting force, may be applied to the engagement sleeve portion 307 when engaged with the plug connector **P**. The forces generated by repeated removal and insertion may weaken the drawn portions of the connector.

Also, in these type of connectors, it has been found that there is room for improvement by reducing the connector size and the overall weight of the connector, while still maintaining the electrical performance of the shield. The conventional connector housing used with such connectors is formed substantially into a box-like shape with six surfaces. In view of the inherent function of the insulative housing, it is sufficient to have the housing to support the shield member in its extent around the housing and its internal contacts, as well as supporting the contacts. In the aforementioned conventional connectors, although the housing has structure supports the metal shield and has a desired mechanical strength, it has an unnecessarily large thickness for its structural stability. This creates a problem that inhibits the goal of attaining further miniaturization and weight reduction.

① Additionally, in this type of connector where repeated removal and insertion of the plug connector **P** to the receptacle connector **R** occurs, frictional wear or deformation can occur with the drawn engagement portions, so that there is a fear that the contact stability between the shield members of the plug and receptacle connectors is gradually reduced over time, and frictional wear may result in a displacement between the two respectively engaged shields, reducing the mechanical stability of the two connectors. For this reason, depending on the frequency and condition of the insertion/removal of the two connectors, there is another fear that either the grounding stability of the overall connector system will be degraded (i.e., the ability of electrical noise to be led by the shields to a ground on the circuit board) as well as the stability of the engagement between the two connectors.

002160-88809960

Yet another object of the present invention is to provide a reduced size and weight USB style connector in which the connector includes a housing formed from electrically insulative material, the connector housing having a body portion that supports a plurality of conductive terminals thereon, the connector housing further including top and bottom walls extending forwardly from the housing body portion in a cantilevered fashion, and the connector housing not having any vertical sidewalls for joining the top and bottom walls together, the connector further including a conductive metal shell encircling most of the exterior surface of the connector body, the shell including a top plate, a front plate and two side plates that are formed around the top and bottom plates and the connector body, the metal shell side plates defining the sidewalls of the receptacle of the connector and the metal shell retaining a separate metal shield member in place upon the connector housing.

The present invention accomplishes these and other objects by way of its novel and unique structure, utilizing the following means to solve the aforementioned problems. A first means of the present invention is characterized by way of a shielded connector having an insulative housing supporting at least one conductive terminal, and a shield member that overlies a surface of the connector housing, the shield member having a

With this second means, the spring portions are provided on the side surface shield portions and because the connector housing has no sidewalls, the spring portions may be brought into contact with the opposing left and right side surfaces of the plug connector to thereby will hold the plug connector effectively in a stable condition, without any rattling or displacement. Thus, the electrical connection effected by the connector is stable in a manner in which any transmitted electrical noise is passed directly to the ground located on the circuit board to which the receptacle connector is mounted. The spring portions are brought into contact with the side surfaces of the opposing plug

A third means of the present invention is characterized in that another engagement piece is provided on the top of the receptacle connector that engages with a recessed portion of the surface of the opposing plug connector. This third engagement piece is guided into the insulating housing of the connector through an opening that is formed in the top plate portion of the connector housing. According to this means, the engagement piece is provided on the top surface shield portion of the metal shield so that it will engage the recessed portion of the surface of the plug connector to hold the plug connector in place within the receptacle connector. In addition to the positioning of the opposing connector caused by the left and right side spring pieces, this engagement piece provides a further positioning along the top face of the plug connector to hold the plug connector in place within the receptacle connector. The three engagement pieces exert a force on the plug connector in three directions, so that the stability of the connector during repeated insertion and removal is enhanced, as well as the electrical connection between the plug and receptacle connectors. The top plate portion of the connector housing is formed with an opening for receiving the engagement piece within the confines of the connector housing, so that this opening further contributes to the weight reduction obtained with the present invention.

ADDED

These and other objects, features and advantages of the present invention will be clearly understood through consideration of the following detailed description.

00E160 28809960

Brief Description of the Drawings

FIG. 1 is a perspective view of a receptacle connector for mounting on a circuit board which is constructed in accordance with the principles of the present invention;

FIG. 2 is a front end view of the connector of FIG. 1;

FIG. 3 is a sectional view of the connector of FIG. 2, taken along lines 3-3 thereof;

FIG. 4 is a sectional view of the connector of FIG. 2, taken along lines 4-4 thereof;

FIG. 5 is a side view of the connector of FIG. 1;

FIG. 6 is a top plan view of the connector of FIG. 1;

FIG. 7 is a bottom plan view of the connector of FIG. 1;

FIG. 8 is a sectional view of the connector of FIG. 6, taken along lines 8-8 thereof;

FIG. 9 is a sectional view of the connector of FIG. 6, taken along lines 9-9 thereof;

FIG. 10 is a plan view of a metal blank that is formed into the metal shell utilized on the connector of FIG. 1;

FIG. 11 is a front end view of the metal shield of FIG. 10 that is placed onto the connector housing of the connector of FIG. 1;

FIG. 12 is a sectional view of the metal shield of FIG. 11, taken along lines 12-12 thereof;

FIG. 13 is a top plan view of the metal shield of FIG. 11;

FIG. 14 is a side view, taken from the right, of the metal shield of FIG. 11;

FIG. 15 is a perspective view of a prior art shielded receptacle connector: and,

FIG. 16 is a perspective view of a prior art shielded plug connector.

Detailed Description of the Preferred Embodiments

Sub.
A1

An improved shielded connector **R** constructed in accordance with the principles of the present invention is illustrated in FIGS 1-14 and in the embodiment shown, a "DIP" type electrical connector of USB style is illustrated as an example of a connector to which the principles of the present invention may be applied. The connector shown is one that is intended to be mounted on a substrate, such as a circuit board (not shown). As illustrated in FIGS. 1-3, the shielded connector **R** is provided with an inner insulative housing for supporting one or more conductive terminals or contacts 1, and a metal shell 20 for overlying the outer surface of the connector housing to thereby shield the terminal 1. The metal shell 20 includes a front frame panel portion 22 that defines an opening 21 in the shell 20 and the connector **R**. This opening 21 receive a portion of an opposing plug connector **P**, such as the one shown in FIG. 16. The front frame portion 22 can be seen to entirely surround the opening 21.

The front frame portion 22 is formed as a single, seamless piece and it surrounds the entire extent, or circumference, of the opening 21 of the connector **R**. The front frame portion 22 may include, if desired, a convex portion 22a that has a profile greater than that of the frame, i.e., is larger than it, so as to form a polarizing feature at the opening 21 that mates with a corresponding recessed portion of the opposing plug connector **P**. The opposing plug connector **P** will be substantially the same in size and detail as that shown in FIG. 16, so that it is not necessary to reproduce it here.

The insulative housing 10 of the connector has a box-like shape with a plurality of openings. The housing 10 is preferably formed by molding from a resin or plastic that possesses a high mechanical strength. As can be seen from FIGS. 3, 4 8 and 9, the connector housing 10 has a top plate, or wall portion, 10a that forms a part of its top surface, a bottom plate, or wall portion, 10b that forms a part of the bottom surface of the connector housing, a front surface, or wall portion, 10c with an insertion opening 21 formed therein for receiving a leading portion of the opposing plug connector **P**, and a

rear body portion 10d having an extended opening 11a through which the conductive terminals 1 extend for connection to a circuit board (not shown). The top and bottom wall portions 10a, 10b are cantilevered out from the rear body portion 10d. These terminals 1 may include solder tails that may be surface mounted to the circuit board, or as illustrated, they may include the through-hole tails illustrated. Importantly, and as explained in greater detail below and as illustrated in FIGS. 8 & 9, the housing 10 is formed with out any sidewalls, or side plate portions. Rather, it has a general U-shape in cross-section, as shown in FIG. 4 with a terminal support wall portion 11 disposed between the top and bottom wall portions 10a, 10b. The terminal support wall portion 11 is also cantilevered from housing rear body portion 10d.

Turning now to FIG. 3, the housing 10 includes an opening 10e in its top surface that receives the engagement portion 32 of a metal shield 30 that is applied to the top plate portion 10a of the housing 10. This top plate portion 10a includes a front portion 10c (FIG. 3) that has a thin recessed portion 10f formed therein which approximately matches the thickness of the metal shell 20. This is because the metal shell 20 extends partially over the metal shield 30 and accordingly, the thickness of the top plate portion 10a is reduced so that the exterior surface of the metal shell 20 will be flush with the surface of the metal shield 30.

As mentioned above, no sidewalls are formed in the housing 10, and therefore as illustrated in FIG. 4 the top plate portion 10a and the bottom plate portion 10b of the housing 10 extend out from the rear body portion 10d of the housing 10 in a cantilevered fashion. For stability purposes, the housing rear body portion 10d preferably has a large thickness as compared to the plate portions for the purpose of enhancing the mechanical strength of the connector housing 10.

The connector housing 10 has a substantial box-like shape and is provided in its interior portion with an inner or central terminal support portion 11 that supports one or more conductive terminals 1 in the connector housing 10. The terminals are shown best

in FIG. 3 and each terminal includes an extended, curved contact portion 3 formed along the body thereof and a tail portion 4 that extends out of the connector housing 10. The housing terminal support portion 11 has an opening that receives the terminal and includes a ledge or end portion 13 against which a free end 2 of the terminal 1 bears. The contact portion 3 of the terminal protrudes through the bottom of the terminal support portion 11 and extends into part 12 of the connector insertion opening. The curved contact portion 3 is formed near the free end 2 of the terminal 1, so that the spring effect that ensures good contact between the terminal 1 and a facing terminal of an opposing connector **P** is enhanced.

The tail portions 4 of the terminals 1 exit the housing 10 by way of a rear passage or port 11a, and may be bent downwardly to extend straight and project through the lower part of the connector housing 10. The tails 4 may extend straight as illustrated for insertion into a through hole formed in the circuit board to which the connector is mounted or they may be bent into a horizontal plane for soldering to contact pads on the circuit board. The receptacle connector **R** illustrated is shown as a four-pin connector having four terminals 1 arranged within the connector housing 10. In order to avoid bunching of the terminal tails 4, the tails are staggered as shown in FIG. 3. Other terminal arrangements and types are contemplated.

The metal shell 20 is formed after it is stamped out of a suitable metal blank by bending it. The metal blank 20A is illustrated in plan view in FIG. 10. It can be seen to include a plurality of panels that are integrally attached to each other, such as a front surface shield panel, or portion 23 indicated at ①, two side surface shield panels, or portions 24 on both sides of the front surface but spaced apart therefrom as indicated at ②, a top surface shield panel, or portion 25 as indicated by ③, a bottom surface shield portion 26 as indicated at ④, two engagement pieces 27 as indicated by ⑤ and fixing pieces 28 as indicated by ⑥. All these panels and portions form the part of the metal shell that overlies the outer surfaces of the connector housing 10. These overlying portions

0065088091300

Sub.
A2

Something
Added

③

09680-0370

13

Swedish added

Swedish added

In this embodiment, the sidewalls of the connector housing 10 are omitted (i.e., open) so that the connector housing 10 itself may be reduced both in size and in weight. The window in the top wall member also assists in reducing weight of the connector **R**. This permits the connector to achieve the goal of significant reduction size and in weight to the point where connectors of the present invention may be made at one-third the size of comparable conventional connectors shown in FIG. 15. The overall mechanical strength of the connectors of the invention is not affected because the open sides of the connector housing 10 are covered by the side surface shield portions 24 of the metal shell 20 as well as the side surfaces 33 of the metal retainer shield 30, so that the electrical and mechanical performance of the connector is maintained.

[illegible]

The spring pieces 34 themselves contact the outer surface of the plug connector shell 310 and serve to stabilize the frictional resistance that occurs during insertion and removal of the plug connector **P**. These spring pieces 34 are disposed on the right and left sides of the connector housing 10 and clamp and hold the plug shell 310 on both right and left sides thereof, and as shown in FIG. 9, this clamping occurs at a level at or above the level of support for the contact portions 3 of the terminals 1. These two spring pieces enhance both the grounding aspect of the two connectors and the stability of the connector **R** during insertion and removal of the plug connector **P** therefrom.

16

While the preferred embodiment of the invention have been shown and described, it will be apparent to those skilled in the art that changes and modifications may be made therein without departing from the spirit of the invention, the scope of which is defined by the appended claims.